ThinkPad X280 Platform Specifications

Processor	7th Generation I			rocessor NEA; i5-7200U is NC	OT available ir	o US	Weight	WxDxH: 12.11" x 8.26" x 0.69-0.70"; 307.7mm x 209.8mm x 17.4-17.8mm FHD non-touch model: 2.49 lb / 1.13 kg; HD non-touch model: 2.78 lb / 1.26 kg; FHD multi-touch model: 2.79 lb / 1.27 kg	
	Processor # of	# of	Base	Max Turbo Frequency Cache	1 14	Processor Graphics			
	i3-7020U i3-7130U i5-7200U 2	4	2.3 GHz 2.7 GHz 2.5 GHz	- 3MB - 3MB 3.1 GHz 3MB	DDR4-2133	Intel HD Graphics 620	Case color Case material	Black Display cover: Carbon Fiber (FHD non-touch model) or Glass Fiber (HD & FHD multi-touch model); Bottom: Magnesium/Aluminum	
	i5-7300U		2.6 GHz	3.5 GHz 3MB				rOptional: Smart card reader	
	or 8th Generation Intel Core i3 / i5 / i7 Processor							MicroSD card reader, in the combo slot with nano-SIM card Two USB 3.1 Gen 1 (one Always On),	
	Processor # of Number Cores i3-8130U 2	# of Threads		Max Turbo Frequency Cache 3.4 GHz 4MB	Memory Types	Processor Graphics	-	one USB 3.1 Type-C Gen 1 (with the function of Power Delivery and DisplayPort), one USB 3.1 Type-C Gen 2 / Thunderbolt 3 (with the function of PD and DP),	
	i5-8250U i5-8350U i7-8550U i7-8650U	8	1.6 GHz 1.7 GHz 1.8 GHz 1.9 GHz	3.4 GHz 4MB 3.4 GHz 6MB 3.6 GHz 6MB 4.0 GHz 8MB 4.2 GHz 8MB	DDR4-2400	Intel UHD Graphics 620	Monitor cable	HDMI 1.4b, Ethernet extension connector, combo slot of nano-SIM card (WWAN models) and microSD card reader, headphone / microphone combo jack, optional smart card reader, side docking connector, security keyhole *Depending on many factors, actual data transfer speed may be lower than theoretical speed HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter	
Graphics	Intel HD Graphics 620 or Intel UHD Graphics 620 in processor; supports external digital monitor via HDMI or USB Type-C; supports three independent displays; Max resolution: 4096x2304@60Hz (USB Type-C); 4096x2160@30Hz (HDMI)					30Hz (HDMI)	(optional) Bundled Accy	USB-C to VGA: Lenovo USB-C to VGA Adapter USB-C to DP: Lenovo USB-C to DisplayPort Adapter ccy Optional: ThinkPad Ethernet Extension Adapter Gen 2	
Chipset Memory	Intel SoC (System on Chip) platform 4GB, 8GB, or 16GB / 2400MHz DDR4 / soldered to systemboard, no sockets * 4GB memory is NOT available in US and EMEA * System clocks down for processors with lower memory controller					, ,	Audio support	stereo speakers, 2W x 2, Dolby® Audio™ Premium / dual array microphone (for special bid model, microphone is optional), headphone / microphone combo jack	
Display	Some: 12.5" (317.5mm) HD (1366x768), anti-glare, LED backlight, 220 nits, 16:9 aspect ratio, 400:1 contrast ratio					•			
Multi-touch (opt)	Some: 12.5" (317.5mm) FHD (1920x1080), anti-glare, LED backlight, WVA, 300 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing angle On-cell touch, supports 10-finger gesture (FHD only)						Keyboard UltraNav™	6-row, spill-resistant, multimedia Fn keys, optional LED backlight TrackPoint®pointing device and buttonless Mylar surface multi-touch touchpad	
Walli-todon (opt)	* FHD non-touch model is NOT available in US						Security Security chip	Power-on password, hard disk password, supervisor password, security keyhole bip Discrete TPM 2.0, TCG Certified (may be disabled in some region)	
Storage	One of the following, configurable by model: • M.2 SSD / SATA 6.0Gb/s (e.g. xxxGB SSD M.2) • M.2 SSD / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s (e.g. xxxGB SSD M.2 PCIe NVMe)					M 2 PCIa NVMa)	vPro <i>(óptional)</i> Intel vPro Technology Fingerprint reader <i>Optional:</i> Touch style match on chip fingerprint reader on the palm rest,		
Optical	, , , , , , , , , , , , , , , , , , , ,					wi.21 Ole INVIVIE)	NFC (optional)	anti-spoofing technology Near Field Communication	
Ethernet	Native Intel Ethernet Connection I219-V (<i>Non-vPro</i>) or I219-LM (<i>vPro</i>) via optional ThinkPad Ethernet Extension Adapter Gen 2						Battery	Integrated Li-ion 48Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter	
WLAN (optional) Bluetooth™ (opt)	Intel Dual Band Wireless-AC 8265, Wi-Fi 2x2 802.11ac + Bluetooth 4.1, M.2 card Bluetooth 4.1 wireless, integrated in Wi-Fi + Bluetooth combo adapter						Max battery life AC adapter	MobileMark® 2014: 16.6 hr *Battery life varies significantly with hardware configurations, settings, usage, & other factors 45W or 65W USB-C AC adapter	
WWAN (optional)	• Wireless WAN upgradable (special bid only) • Integrated Mobile Broadband 4G LTE, Intel XMM™ 7262 (Fibocom L830-EB), M.2 card (EMEA only) • Integrated Mobile Broadband 4G LTE-A, Intel XMM™ 7360 (Fibocom L850-GL), M.2 card * For non-WWAN model, it means the model is NOT WWAN upgradable Nano-SIM card slot, in the combo slot with microSD card reader, optional Verizon LTE (US) SIM card						l	•	
SIM card (opt)							Limited warranty	Optional: Windows® 10 Home 64 or Windows 10 Pro 64 One of the following, configurable by model: 1-year depot repair service -1-year depot with 2-year system board repair service -1-year/3-yr battery depot repair service -1-year + 2-year depot repair service -1-year + 2-year limited onsite service -3-year/1-yr battery depot repair service -3-year/3-yr battery depot repair service	
							Mil-Spec test	3-year/1-yr battery limited onsite service 3-year/3-yr battery limited onsite service MIL-STD-810G military testing	
							Mil-Spec test		
Niete The energia	tions above may r		المصلحال	aniana anal mi-l-t	-l	niana	Environment	EPEAT™ Gold (US only); ENERGY STAR® 6.1; RoHS-compliant Lenov	